




<b>SECTION I. IDENTIFICATION</b>	
<b>Name of the Manufacturer:</b>	<b>SICAMU Inc.</b>
<b>Commercial name:</b>	<b>Engine Degreaser</b>
<b>Address:</b>	<b>Manufacturer:</b> 1066 Strong Road, Quincy, FL, 32351 Telf.: +1 (850) 270.62. 83 Fax: +1 (850) 875.45.18
<b>Type of product:</b>	Degreaser, car care.

<b>SECTION II. HAZARD IDENTIFICATION</b>	
<b>Hazard classification:</b>	GHS-US Classification Flam. Aerosol 2 Dissolved gas Asp. Tox 1
<b>Label Elements:</b>	   GHS02      GHS04      GHS08
<b>Hazard Statement:</b>	Flammable aerosol. Contains gas under pressure, may explode if heated. May be fatal if swallowed or if it enters airways. Appearance: black      Physical state: liquid      Odor: solvent Health hazard: 2      Flammability: 2      Instability: 0
<b>Precautionary Statements (prevention):</b>	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use
<b>Precautionary Statements (response):</b>	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store locked up. Store in a well-ventilated place. Protect from sunlight.
<b>Storage and disposal:</b>	Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local, regional, national and/or international regulation.
<b>Hazards not otherwise classified</b>	None known.



Sicamu, Inc.  
1066 Strong Road  
Quincy, FL, 32351  
850-2706283

(HNOC) other  
information

### SECTION III. COMPOSITION/INFORMATION ON INGREDIENTS

Name	CAS	% Weight
Petroleum distillates, hydrotreated light	64742-47-8	30-50
Solvent naphtha, petroleum heavy aromatic	64742-94-5	20-30
2-propanone	67-64-1	5-10
Poly(oxy-1,2-ethanediyl), alpha-(4-nonylphenyl)-omega-hydroxy-, branched	127087-87-0	2-4
Carbon Dioxide	124-38-9	1-5

### SECTION IV. FIRST-AID MEASURES

<b>Eye contact:</b>	Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Direct contact with the eyes is likely to be irritating.
<b>Skin contact:</b>	If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse
<b>Inhalation:</b>	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
<b>Ingestion:</b>	IF SWALLOWED: immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
<b>Most important symptoms and effects, both acute and delayed:</b>	May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause respiratory tract irritation. May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.
<b>Indication of any immediate medical attention and special treatment if needed:</b>	Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible). SECTION



Sicamu, Inc.  
1066 Strong Road  
Quincy, FL, 32351  
850-2706283

### **SECTION V. FIRE-FIGHTING MEASURES**

<b>Extinguishing media:</b>	Carbon dioxide, dry chemical, halons or foam. Do not use spray water or water jet.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Special hazards arising from the substance or mixture:</b>	Flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon and oxides of nitrogen Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. No dangerous reaction known under conditions of normal use.
<b>Special fire fighting procedures:</b>	DO NOT fight fire when fire reaches explosives. Evacuate area. Exercise caution when fighting any chemical fire. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool

### **SECTION VI. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Collect spillage. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

### **SECTION VII. HANDLING AND STORAGE**



Sicamu, Inc.  
 1066 Strong Road  
 Quincy, FL, 32351  
 850-2706283

<p><b>Precautions for safe handling</b></p>	<p>Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains. For product usage instructions, please see the product label.</p>
<p><b>Conditions for safe storage, including any incompatibilities</b></p>	<p>Level 1 Aerosol. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49 °C/120 °F. Do not handle or store near an open flame, heat or other sources of ignition. Exposure to high temperature may cause can to burst. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).</p>

<p><b>SECTION VIII. EXPOSURES CONTROL/PERSONAL PROTECTION</b></p>		
<p>Petroleum distillates, hydrotreated light (64742-47-8) NA</p>		
<p>Solvent naphtha, petroleum, heavy aromatic (64742-94-5) NA</p>		
<p>2-propanone (67-64-1)</p>		
<p>8 Hr TWA PEL (OSHA) (mg/m<sup>3</sup>)</p>	<p>1000</p>	
<p>8 Hr TWA TLV (ACGIH) (ppm)</p>	<p>500</p>	
<p>STEL TLV (ACGIH) (ppm)</p>	<p>750</p>	
<p>Poly(oxy-1,2-ethanediyl), alpha-(4- nonylphenyl)-omega-hydroxy-, branched (127087-87-0)        May include traces of Polyethylene Glycol (lower than 0.3%)</p>		
<p>TWA 8 hours AIHA WEEL 10 mg/m<sup>3</sup></p>		
<p>Carbon dioxide (124-38-9)</p>		
<p>ACGIH</p>	<p>ACGIH TWA (ppm)</p>	<p>5000</p>
<p>ACGIH</p>	<p>ACGIH STEL (ppm)</p>	<p>30000</p>
<p>OSHA</p>	<p>OSHA PEL (TWA) (mg/m<sup>3</sup>)</p>	<p>9000</p>
<p>OSHA</p>	<p>OSHA PEL (TWA) (ppm)</p>	<p>5000</p>



Sicamu, Inc.  
1066 Strong Road  
Quincy, FL, 32351  
850-2706283

Exposure controls	
Appropriate engineering controls	Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Hand protection	Wear chemically resistant protective gloves.
Eye protection	Safety glasses or goggles are recommended when using product.
Skin and body protection	Wear suitable protective clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	Maintain levels below Community environmental protection thresholds.
Other information	Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

#### **SECTION IX. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Clear.
Odor	Solvent.
Odor threshold	No data available
pH	Not available.
Melting point/freezing point /boiling point	No data available
Flash point	>141 F
Evaporation rate	No data available
Flammability (solid, gas)	Flammable aerosol.
Vapor pressure	No data available
Relative vapor density at 20 °C	No data available
Relative density :	0.86
Solubility	No data available
Partition coefficient n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	No data available
Explosive limits	No data available
Explosive properties	No data available
Oxidizing properties	No data available



Sicamu, Inc.  
1066 Strong Road  
Quincy, FL, 32351  
850-2706283

Heat of Combustion	No data available
Flame Projection	No data available
Flashback	No data available

#### **SECTION X. STABILITY AND REACTIVITY**

<b>Reactivity:</b>	Stable.
<b>Chemical stability:</b>	Stable under normal storage conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.
<b>Possibility of hazardous reactions:</b>	None known under normal use.
<b>Incompatible materials</b>	Strong oxidizing agents. Strong acids. Strong bases.
<b>Hazardous decomposition:</b>	May include, and are not limited to: oxides of carbon and oxides of nitrogen.

#### **SECTION XI. TOXICOLOGICAL INFORMATION**

Toxicological effects	
Distillates petroleum, hydrotreated light (64742-47-8)	
LD50 oral rat	>5000 mg/kg
LD50 dermal rabbit	>2000 mg/kg
LC50 inhalation rat	>5.2 mg/l exposure 4 hours
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
LD50 oral rat	>5000 mg/kg
LD50 dermal rabbit	>2 ml/kg
LC50 inhalation rat	>590 mg/m <sup>3</sup> exposure 4 hours
Skin corrosion/irritation Serious eye damage Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity	Not classified



Sicamu, Inc.  
1066 Strong Road  
Quincy, FL, 32351  
850-2706283

Reproductive toxicity	
Specific target organ (single exposure)	
Specific target organ (repeated exposure)	
Aspiration hazard	May be fatal if swallowed and enter airways
Symptoms/injuries after inhalation	May cause respiratory tract irritation
Symptoms/injuries after skin contact	May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin
Symptoms/injuries after eye contact	May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling
Symptoms/injuries after ingestion	May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.
Other information	Likely routes of exposure: ingestion, inhalation, skin and eye.
<p><b>Exposure routes:</b> Inhalation, Skin Contact, Eye Contact</p> <p><b>Information on toxicological effects</b></p> <p><u>2-propanone (CAS No. 67-64-1)</u></p> <p><b>Acute toxicity</b> Oral LD50 = 5800 mg/kg (rat) Dermal LD50 &gt;15800 mg/kg (rabbit) Inhalation LC50 76 mg/L (4 hour(s)) (rat) - Vapours may cause drowsiness and dizziness</p> <p><b>Irritation / Corrosivity</b> Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking.</p> <p><b>Sensitisation</b> It is not a skin sensitiser.</p> <p><b>Repeated dose toxicity</b> Oral NOAEL = 900 mg/kg/day (rat) (90-days) Inhalation NOAEL ≥ 19,000 ppm (rat)</p> <p><b>Carcinogenicity</b> It is unlikely to present a carcinogenic hazard to man.</p>	
<p>Poly(oxy-1,2-ethanediyl), alpha-(4- nonylphenyl)-omega-hydroxy-, branched (127087-87-0)</p> <p>Peroral</p> <p>Rat; male; LD50 = 5.61 (3.16 - 9.98) ml/kg</p> <p>Time to Death: Death at 1-9 days</p> <p>Major Signs: prostration, shallow breathing</p> <p>Gross Pathology - Decedents: gastro-intestinal distention, vascular dilatation; congestion of kidneys, adrenals</p> <p>Gross Pathology - Survivors: Nothing remarkable.</p> <p>Percutaneous</p> <p>Rabbit; male; LD50 = 4.00 (2.45 - 6.53) ml/kg; 24 hr occluded contact.</p>	



Sicamu, Inc.  
1066 Strong Road  
Quincy, FL, 32351  
850-2706283

Time to Death: Death at 2-6 days  
Major Signs: none before death  
Irritation: red-brown discoloration, tough texture, desquamation  
Gross Pathology - Decedents: congestion of lungs, livers, spleens, kidneys; gray discoloration, vascular dilatation of stomachs  
Gross Pathology - Survivors: Nothing remarkable. Inhalation Saturated Vapor Studies dynamic generation Rat; female; LT50; > 6 h Mortality: 0/6 Time to Death: No information available.  
Gross Pathology: Nothing remarkable.  
**IRRITATION**  
Skin: Rabbit; unoccluded contact; 0.01 ml  
Results: moderate capillary dilatation at 24 hr  
Eye: Rabbit; 0.5 ml; 15% in water  
Results: severe corneal injury, iritis within 24 hr  
Eye: Rabbit; 0.005 ml  
Results: severe corneal injury, iritis within 24 hr  
Eye: Rabbit; 0.5 ml; 5% in water  
Results: trace corneal injury within 24 hr

## SECTION XII. ENVIRONMENTAL INFORMATION

Ecology-general	May cause long term adverse effects in the aquatic environment.
Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 fish 1	45 mg/l (exposure time 96 hours, specie Pimephales promelas)
LC50 fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Solvent Naphtha, petroleum, heavy aromatic (64742-94-5)	
LC50 fish 1	19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	0.95 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	2.34 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Persistence and biodegradability	Not established
Bio accumulative potential	Not established
Petroleum distillates, hydrotreated light (64742-47-8) Bio accumulative potential	
BCF fish 1	61-159
Solvent naphtha, petroleum, heavy aromatic (64742-94-5) Bio accumulative potential	
BCF fish 1	61-159
Partition coefficient n-octanol/water	2.9-6.1
Carbon dioxide (124-38-9)	
BCF fish 1	No bio accumulation.





Sicamu, Inc.  
1066 Strong Road  
Quincy, FL, 32351  
850-2706283

Mobility in soil	No data available.		
Other adverse effects	No known effects on global potential. Avoid release to the environment.		
2-propanone (CAS 67-64-1)			
Ecology-general	Not classified as dangerous for the environment according to the criteria of Directive 67/548/EEC. Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008.		
Ecology-air	Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009). Not included in the list of substances which may contribute to the greenhouse effect (Regulation (EC) No 842/2006). TA-Luft Klasse 5.2.5.		
Ecology-water	Not harmful to fish (LC50(96h) >1000 mg/l). Not harmful to invertebrates (Daphnia). Not harmful to algae (EC50 >1000 mg/l). Not harmful to plankton. Inhibition of activated sludge.		
LC50 fish 2	5540 mg/l (LC50; EU Method C.1; 96 h; Salmo gairdneri; Static system; Fresh water; Experimental value)		
EC50 Daphnia 2	12600 mg/l (LC50; Other; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)		
Persistence and biodegradability			
Persistence and biodegradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No test data on mobility of the substance available.		
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance		
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance		
ThOD	2.20 g O <sub>2</sub> /g substance		
BOD (% of ThOD)	0.872 (20 days; Literature study)		
Bio accumulative potential			
BCF Fish 1	0.69 (BCF)		
BCF other aquatic organisms 1	3 (BCF: BCFWIN)		
Log Pow	-0.24 (test data)		
Bio accumulative potential	Not bio accumulative		
Mobility in soil			
Surface tension	0.0237 N/m		
Poly(oxy-1,2-ethanediyl), alpha-(4-nonylphenyl)-omega-hydroxy-, branched (127087-87-0)			
Environmental fate:			
BOD (% Oxygen consumption)			
Day 5	Day 10	Day 20	
4%	15%	34%	
Ecotoxicity			
Toxicity to Micro-organisms Bacterial Inhibition; 16 h; IC50	Toxicity to Micro-organisms Bacterial/NA; 18 h; IC50	Toxicity to Aquatic Invertebrates Daphnia; 48 h; LC50 Result value: 4.9 (3.8 - 6.2) mg/l	Toxicity to Fish Fathead Minnow; 96 h; LC50 Result value: 2.34 (2.1 - 2.6) mg/l



Sicamu, Inc.  
1066 Strong Road  
Quincy, FL, 32351  
850-2706283

Result value: > 1000 mg/l	Result value: > 1000 mg/l		
---------------------------	---------------------------	--	--

### **SECTION XIII. DISPOSAL INFORMATION**

**Disposal:** Material used to contain large spills should be disposed in accordance with local laws and regulations. Do not dispose into environment, in drains or in water courses.  
Disposal should be in accordance with applicable regional, national regulations.  
Do not reuse container.

### **SECTION XIV. TRANSPORT INFORMATION**

Department of Transportation (DOT)  
In accordance with DOT  
Transport document description : Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1  
UN-No.(DOT) : UN1950  
Proper Shipping Name (DOT) : Aerosols flammable, (each not exceeding 1 L capacity)  
Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115  
Hazard labels (DOT) : 2.1 – Flammable gas



Other information : No supplementary information available.  
Special transport precautions : Do not handle until all safety precautions have been read and understood.

### **SECTION XV. REGULATORY INFORMATION**

US Federal regulations:  
All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

International regulations:  
No additional information available.

US States regulations



Sicamu, Inc.  
 1066 Strong Road  
 Quincy, FL, 32351  
 850-2706283

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm.

Naphthalene (91-20-3)

U.S. - California - Proposition 65 - Carcinogens List	Yes
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
Non-significant risk level (NSRL)	5.8 µg/day

2-propanone (CAS #67-64-1)  
 Listed on the US TSCA (Toxic Substance Control Act) inventory  
 RQ (Reportable quantity, section 304 of EPA's list of lists) 5000 lb  
 SARA Section 311/312 Hazard Classes: Immediate (acute) health hazard. Fire hazard.  
 All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Poly(oxy-1,2-ethanediyl), alpha-(4- nonylphenyl)-omega-hydroxy-, branched (127087-87-0)  
 This product contains the following substances subject to CERCLA Section 103 reporting requirements and are listed in 40 CFR Part 302.4.

Component	CAS #	Amount
Glycol Ethers	Not available	<= 0.3%
1,4-Dioxane	123-91-1	<= 0.0020%
Ethylene oxide	75-21-8	<= 0.0010%
Acetaldehyde	75-07-0	<= 0.0005%
Formaldehyde	50-00-0	<= 0.0005%

This product does not contain substances subjected to SARA section 302 reporting requirements listed in 40 CFR Part 302.4

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act 1986 and 40 CFR Part 372:

Glycol Ethers (CAS # Not available) <= 0.3%  
 SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT) SECTIONS 311 AND 312  
 Delayed (Chronic) Health Hazard : Yes  
 Fire Hazard : No  
 Immediate (Acute) Health Hazard : Yes  
 Reactive Hazard : No  
 Sudden Release of Pressure Hazard : No



Sicamu, Inc.  
 1066 Strong Road  
 Quincy, FL, 32351  
 850-2706283

**TOXIC SUBSTANCES CONTROL ACT (TSCA)** All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

State/local

**PENNSYLVANIA (WORKER AND COMMUNITY RIGHT-TO-KNOW ACT)** The following product components are cited in the Pennsylvania Hazardous Substances List, the Pennsylvania Special Hazardous Substance List, and/or the Pennsylvania Environmental Hazardous Substance list, and are present at levels which require reporting.

Component	CAS #	Amount
Glycol Ethers	Not available	<= 0.3%

**MASSACHUSETTS (HAZARDOUS SUBSTANCES DISCLOSURE BY EMPLOYERS)** The following components of this product appear on the Massachusetts Substance List and are present at levels which could require identification in the SDS:

Component	CAS #	Amount
1,4-Dioxane	123-91-1	<= 0.0020%
Ethylene oxide	75-21-8	<= 0.0010%
Acetaldehyde	75-07-0	<= 0.0005%
Formaldehyde	50-00-0	<= 0.0005%

**CALIFORNIA PROPOSITION 65 (SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986)** This product contains the following chemical(s) known to the State of California to cause cancer:

Component	CAS #	Amount
1,4-Dioxane	123-91-1	<= 0.0020%
Acetaldehyde	75-07-0	<= 0.0005%
Formaldehyde	50-00-0	<= 0.0005%

**CALIFORNIA PROPOSITION 65 (SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986)** This product contains the following chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

Component	CAS #	Amount
Ethylene oxide	75-21-8	<= 0.0010%

Carbon Dioxide (124-38-9)

US. New Jersey Right to know hazard substance list

US. Pennsylvania Right to know list

**SECTION XVI. OTHER INFORMATION**

**Distributed by:** Authorized dealers.

**Written by:** Antonio Pons, Technical Director, VP of Operations

**Date:** January 02, 2.017

**Guarantee waiver:**



Sicamu, Inc.  
1066 Strong Road  
Quincy, FL, 32351  
850-2706283

This information is accurate and reliable to the best knowledge of Sicamu Inc. No representation, warranty or guarantees are made to its accuracy, reliability or completeness. All users are encouraged to review this SDS in the context of how to use and handle this product. Users are responsible for any interpretation and/or use of this information and of this product. If clarification or further information is required, the user is responsible for contacting Sicamu Inc. to receive any additional information that he may require. Our responsibility for products sold is subject to our standard terms and conditions. A copy of which is available on request.