



Sicamu, Inc.
1066 Strong Road
Quincy, Fl, 32351
850-2706283

SECTION I. IDENTIFICATION

Name of the Manufacturer: SICAMU Inc.

Commercial name: SQ Liquid Wiper

Address:
Manufacturer:
1066 Strong Road, Quincy, Fl, 32351
Telf.: +1 (850) 270.62. 83
Fax: +1 (850) 875.45.18

Type of product:
Silicone polymers in Ethanol.
Clears windshield of rain, snow and sleet. Reduces glare.

SECTION II. HAZARD IDENTIFICATION

Health (NFPA): 2 Flammability (NFPA):3 Reactivity (NFPA):0

POTENTIAL HEALTH EFFECTS

Eye contact: It will cause red eyes and irritation.

Skin contact: It may cause irritation.

Ingestion or inhalation: There is no reason for this product to be ingested, but if it occurs, it may produce gastrointestinal irritation, headaches, fatigue or fainting.

Ventilation: It's recommended to use this product in open areas or places with adequate ventilation.

SECTION III. COMPOSITION/INFORMATION ON INGREDIENTS



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283


Component	Cas Number	% weight
Ethyl Alcohol	64-15-5	<85%
Isopropyl Alcohol	67-63-0	>4%

SECTION IV. FIRST-AID MEASURES

Eye contact:	Rinse with abundant water for several minutes. Get medical attention if irritation lasts more than 15 minutes.
Skin contact:	Rinse skin with soap and water. Clean clothes before using them again. Clean leather clothing with compressed air.
Inhalation:	No first aid required. If the user has any difficulty breathing, it's recommended to move to a well ventilated area.
Ingestion:	Induce vomit. Rinse mouth with water, drink water, and contact a physician.

SECTION V. FIRE-FIGHTING MEASURES

Extinguishing media:	Use carbon dioxide (CO ₂) or dry chemicals for small fires. Use foam or water for large fires.
Special fire fighting procedures:	Self-contained breathing apparatus and protective clothig should be worn. Static electricity is not expected to build up. Product is sensitive to static, make sure all containers are grounded before pumping or pouring liquid.
Classification of risk:	
0 = Minimal	
1 = Low	
2 = Moderate	
3 = High	
4 = Extreme	





Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

SECTION VI. ACCIDENTAL RELEASE MEASURES

Product is sold in small containers, and accidental release is not a cause of concern. Use absorbent material to collect and contain for disposal. Wash area with suitable detergent and rinse thoroughly. Consult with State and Federal Regulations for disposal procedures. As with any other chemical product, it is recommended to wear impermeable gloves.

SECTION VII. HANDLING AND STORAGE

Storage temperature:

Max: 49°C (120 F) Min: 0 °C (32 F)

Handling and storage:

Storage in a dry, cool, ventilated area.

Prevent leaks.

Keep away from sparks and ignition sources.

Do not inhale, ingest or squirt to the eyes.

Keep out of the reach of children.

Do not puncture or burn the container.

Do not use on running machines.

Product should not enter in contact with strong acids, strong bases or strong oxidizing agents.

SECTION VIII. EXPOSURES CONTROL/PERSONAL PROTECTION

Eye protection:

Not required under normal circumstances. If allergies are known wear protective goggles.

Skin protection:

Contact should not happen, and if it does it should not trigger reaction. Impermeable gloves are recommended, particularly if allergies are known.

Respiration and ventilation:

Ensure adequate ventilation, but product is not expected to cause any reaction.



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

Ingestion:	Product should never be ingested. If ingested do not incite vomit, prevent swallowing or sucking into lungs.
Exposure limits:	Not established for product as a whole.

SECTION IX. PHYSICAL AND CHEMICAL PROPERTIES			
Boiling point (°C):	-56	Specific weight (water =1):	0.8020 gr/cc
Vapor pressure (mmHg):	33	Color:	Transparent
Vapor density (Air =1):	->1	Odor:	Alcohol odor
pH @ 100%:	4.5	State:	Transparent Liquid
Volatiles % (volume):	->85	Viscosity:	
Water solubility:	Difficult solubility	Pressure:	Not applicable

SECTION X. STABILITY AND REACTIVITY	
Stability:	Stable.
Conditions to avoid:	Do not expose to open flame, do not puncture. Do not squirt on flames or burning materials.
Incompatibilities:	Strong acids, strong bases, strong oxidizing agents.
Fire decomposition:	Silicon dioxide, carbon oxides, trace amounts of formaldehyde may form when heated above 300 F.

SECTION XI. TOXICOLOGICAL INFORMATION	
Accute eye contact:	Causes irritation.



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

Accute and chronicl skin contact:	May cause irritation. No data regarding chronicl contact.
Accute and chronicl inhalation:	May cause mild irritation. No data regarding chronicl inhalation.
Accute and chronicl ingestion:	May cause mild irritation. No data regarding chronicl ingestion.
Exposure limits:	Not stablished for product as a whole for periods shorter to 8 hours.

SECTION XII. ENVIRONMENTAL INFORMATION

Comments:	Product should not be spilled on fresh bodies of water. Prevent wildlife from interacting with this products.
------------------	---

SECTION XIII. DISPOSALL INFORMATION

Disposal:	Cardboard and plastic are recyclable. Material used to contain large spills should be disposed in accordance with local laws and regulations.
------------------	---

SECTION XIV. TRANSPORT INFORMATION

Transportation:	Propper shipping name: Alcohol, N.O.S. (contains Ethyl Alcohol, Isopropyl Alcohol) Hazard technical name: Alcohol Hazard class: 3 UN/NA number: UN 1987 Packaging group: II EPA SARA Title III Chemical Listings: Section 302 Extremely Hazardous substances: none Section 304 CERCLA Hazardous substances: none Section 312 Hazard Class: Acute: yes, Chronic: no, Fire: yes, Pressure: no, Reactive: no Section 313 Toxic chemicals: none present or none present in regulated quantities. Supplemental State Compliance Information
------------------------	--



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

New Jersey: not required to report under this statute.
Pennsylvania: not required to report under this statute.
California Prop 65: none
TSCA Registered: All components of this product are registered in the TSCA Inventory

SECTION XV. REGULATORY INFORMATION

The following chemicals are specifically listed by individual states; other products specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency of your state.

Supplemental State Compliance Information:

New Jersey and Pennsylvania: not required to report under this statute.

California Prop 65: none

SECTION XVI. OTHER INFORMATION

Distributed by: Authorized dealers.

Written by: Antonio Pons, Technical Director, VP of Operations

Date: August 12, 2015

Guarantee waiver:

This information is accurate and reliable to the best knowledge of Sicamu Inc. No representation, warranty or guarantees are made to its accuracy, reliability or completeness. All users are encouraged to review this MSDS in the context of how to use and handle this product. Users are responsible for any interpretation and/or use of this information and of this product.

If clarification or further information is required, the user is responsible for contacting Sicamu Inc. to receive any additional information that he may require.

Our responsibility for products sold is subject to our standard terms and conditions. A copy of which is available on request.