



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

SECTION I. IDENTIFICATION	
Name of the Manufacturer:	SICAMU Inc.
Commercial name:	SQ 5 in 1
Address:	Manufacturer: 1066 Strong Road, Quincy, FL, 32351 Telf.: +1 (850) 270.62. 83 Fax: +1 (850) 875.45.18
Type of product:	Oil. General purpose lubricant oil.

SECTION II. HAZARD IDENTIFICATION	
Statement of hazardous nature:	Health (NFPA): 1 Flammability (NFPA): 1 Reactivity (NFPA): 0
POTENTIAL HEALTH EFFECTS	
Eye contact:	May cause red eyes and irritation.
Skin contact:	Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
Ingestion or inhalation:	Low toxicity if swallowed. Not expected to be inhaled.
Ventilation:	It's recommended to use this product in open areas or places with adequate ventilation.



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

SECTION III. COMPOSITION/INFORMATION ON INGREDIENTS

Name	CAS	% Weight
Mineral oil	8042-47-5	85-99%
Isobutyl Alcohol	78-83-1	3-8%

SECTION IV. FIRST-AID MEASURES

Eye contact:	Rinse with abundant water for several minutes. Get medical attention if irritation lasts more than 15 minutes.
Skin contact:	Rinse skin with soap and water. Clean clothes before using them again.
Inhalation:	No first aid required. If the user has any difficulty breathing, it's recommended to move to a well ventilated area.
Ingestion:	Rinse mouth with water, drink water, contact physician.

SECTION V. FIRE-FIGHTING MEASURES

Extinguishing media:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth only for small fires. Do not use water in a jet.
Special fire fighting procedures:	Self-contained breathing apparatus and protective clothig should be worn.

Classification of risk:


0 = Minimal

1 = Low

2 = Moderate

3 = High

4 = Extreme



SECTION VI. ACCIDENTAL RELEASE MEASURES



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment refer to Section VIII. For disposal refer to Section XIII. Observe the relevant local and international regulations.

Protective measures: avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth or other appropriate barriers.

Clean up methods: slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable materials and dispose properly.

Additional advice: inform local authorities of large spills.

SECTION VII. HANDLING AND STORAGE

Storage temperature:	Max: 49°C (120 F)	Min: 0 °C (32 F)
Handling and storage:	Storage in a dry, cool, ventilated area. Prevent leaks. Keep away from sparks and ignition sources. Do not inhale, ingest or squirt to the eyes. Keep out of the reach of children. Do not puncture or burn the container. Product should not enter in contact with strong acids, strong bases or strong oxidizing agents.	

SECTION VIII. EXPOSURES CONTROL/PERSONAL PROTECTION

Eye protection:	Not required under normal circumstances. Wear safety glasses if splashes are likely to occur.
Skin protection:	Contact should not happen, and if it does it should not trigger reaction. PVC, neoprene or nitrile rubber gloves are recommended if allergies are known.



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

Respiration and ventilation:	Ensure adequate ventilation, but product is not expected to cause any reaction.
Ingestion:	Product should never be ingested. If ingested do not incite vomit, prevent swallowing or sucking into lungs.
Exposure limits:	No biological limit allocated.

SECTION IX. PHYSICAL AND CHEMICAL PROPERTIES

Boiling point (°C):	280	Specific weight (water =1):	0.858 gr/cc
Vapor pressure (PA @ 20 C):	0.5	Color:	Transparent yellow
Vapor density (Air =1):	>1	Odor:	Lime
pH @ 100%:	6.4	State:	Transparent Liquid
Volatiles % (volume):	N/A	Viscosity:	46 mm ² /s @ 40 C
Water solubility:	Insoluble	Vapor pressure:	<0.5 Pa @ 20 C

SECTION X. STABILITY AND REACTIVITY

Stability:	Stable.
Conditions to avoid:	Extremes of temperature and direct sunlight.



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

Incompatibilities:	Strong oxidizing agents.
Fire decomposition:	Not expected during normal storage.

SECTION XI. TOXICOLOGICAL INFORMATION

Accute eye contact:	Causes irritation.
Accute and chronic skin contact:	Expected to be low toxicity. LD 50 > 5000 mg/kg, rabbit. Slightly irritating.
Accute and chronic inhalation:	Not considered to be a hazard. Expected to be irritating.
Accute and chronic ingestion:	Expected to be low toxicity. LD 500 > 5000 mg/kg, rat. Slightly irritating.
Exposure limits:	Not stablished for product as a whole for periods shorter to 8 hours.

SECTION XII. ENVIRONMENTAL INFORMATION

Comments:	Eco toxicological data has not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual components.
Acute toxicity	Poorly soluble mixture, may cause physical fouling of aquatic organisms. expected to be practically non toxic: LL/EL/IL50>100mg/l. It is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l
Mobility	Liquid under most environmental conditions. If it enters soil it will adsorb to soil particles and will not be mobile. Floats on water.
Persistency/degradability	Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment. Contain components with the potential to bio accumulate.



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

Bioaccumulation	Product is a mixture of non-volatile components which are not expected to be released to air in any significant quantity. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.
Other adverse effects	

SECTION XIII. DISPOSAL INFORMATION

Disposal:	Cardboard and plastic are recyclable. Material used to contain large spills should be disposed in accordance with local laws and regulations. Do not dispose into environment, in drains or in water courses.
------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION XIV. TRANSPORT INFORMATION

Transportation:	US Department of Transportation Classification (49CFR) This material is not subjected to DOT regulations under 49 CFR Parts 171-180. IMDG, this material is not classified as dangerous under IMDG regulations. IATA (country variations may apply) this material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.
------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION XV. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Federal Regulatory Status

EINECS All components listed or polymer exempt.

TSCA/TSL All components listed.

Comprehensive environmental release, compensation & liability act (CERCLA)

Cumene (98-82-8) Reportable quantity: 5000 lbs

This material is classified as an oil under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

Under section 311 of the Clean Water Act (CWA) this material is considered an oil. As such, spills into surface waters must be reported to the National Response Center at (800) 424-8802



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

SARA Hazard Categories (311/312)

No SARA 311/312 Hazards

State Regulatory Status

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

This product contains a chemical known to the State of California to cause cancer.

New Jersey, Pennsylvania Right-to-Know chemical list

Mineral Oil (8042-47-5)

Isobutanol (78-83-1)

SECTION XVI. OTHER INFORMATION

Distributed by: Authorized dealers.

Written by: Antonio Pons, Technical Director, VP of Operations

Date: September 9, 2015

Guarantee waiver:

This information is accurate and reliable to the best knowledge of Sicamu Inc. No representation, warranty or guarantees are made to its accuracy, reliability or completeness. All users are encouraged to review this MSDS in the context of how to use and handle this product. Users are responsible for any interpretation and/or use of this information and of this product.

If clarification or further information is required, the user is responsible for contacting Sicamu Inc. to receive any additional information that he may require.

Our responsibility for products sold is subject to our standard terms and conditions. A copy of which is available on request.